



## PROFESSIONAL BIOMETRIC RECOGNITION AND SOLUTIONS SUPPLIER

- ◇ Access Control Systems   ◇ Attendance Management Systems
- ◇ Multi-Location Attendance Solution On Cloud



Face ID



Fingerprint



PIN



CARD



QR Code



Combination



Shenzhen Union Timmy Technology Co., Ltd, established in 2000, is a professional manufacturer engaged in the R&D of different biometric solutions, and Dedicated to the manufacturing and selling of Fingerprint&Face Recognition time attendance, Fingerprint&Face Recognition access control over the past 20 years.

Our factory covers an area of 2,500 square meters with around 100 employees. So far we have obtained the verified certificates of ISO9001, CE, FCC, ROHS, etc., and achieved the Chinese highest manufacturing honor as "National High tech enterprises" in 2017 with more than 10 patents.

Our brand "TIMMY" is well-known in Biometric attendance market of China, and then we formally decide to step out towards the world market in 2017. Each year we will participate in at least 7 overseas exhibitions and totally take one month or more time paying visit to our overseas clients in some countries, So far our products had already exported to over 70 countries and regions, such as Southeast Asia, Middle east, Europe, South Africa and North America.

We have strong capability of Hardware quality control and Multiple OEM software solution. our Sales and technical support are always available to deal with your consult and inquiry, We Commit that our Desktop and Cloud software are free as well as our device SDK that you can use to integrate with your existed system, Our firmware by far can support 18 types of Multi-languages.

You can cooperate with TIMMY in flexible ways, including OEM/ODM, or Brand sales, Project cooperation and Industry application joint development. Every year, More than one hundred clients from different countries will come to visit us. We treat every visitor with our honesty and sincerity, and hold the business belief of win-win cooperation.

It is sincerely welcomed the worldwide friends in the biometric field to visit us!

# Contents



**P/ 01**  
Solutions



**P/ 07**  
Authentication  
Certificate



**P/ 11**  
AI Dynamic Face  
Recognition Terminal



**P/ 16**  
Facial Recognition  
Terminal



**P/ 17**  
Access Control  
System




**P/ 18**  
Attendance  
Management System



**P/ 21**  
QR Code  
Scanner System



**P/ 22**  
WiFi Network,  
Mobile APP Access



**P/ 23**  
Proximity card  
time attendance



**P/ 24**  
Fingerprint  
Reader



**P/ 25**  
Economic Guard  
Tour System



**P/ 26**  
UHF Reader/  
writer



**P/ 27**  
Smart Biomtric  
Door Lock



**P/ 28**  
Card Access  
Control



# Solution



**NPU**  
Neural  
Processing Unit

Faster Speed  
Powerful Feature Extraction  
Improved Adaptability  
Enhanced Security

**AI**

Applications in various  
domains requiring accurate  
and efficient face  
recognition

**23 Years**  
of Experience

**2650m<sup>2</sup>**  
Production Plant

Export To  
**130<sup>+</sup>**  
Countries

**8+3**  
Production+  
QC Lines

TÜVRheinland  
Precisely Right.

Intertek

RoSH

FC

CE

Free  
SDK


Cloud  
Software

Mobile  
APP

Customize  
UI


**ISO 9001**  
Quality Assurance  
Management

**2000**




Company founded and started the sales of time recorder

**2006**




Started developing fingerprint attendance machine

**2009**




Developed color screen series

**2012**




Developed the first standalone attendance machine

**2014**




Developed face recognition products

**2016**




Accelerated global market expansion and launched new products

**2018**




Obtained the national high tech enterprise certificate

**2019**




Developed Dynamic face recognition products

**2020**



Temperature measuring face recognition terminal

**2021-2023**






AI Face Recognition Series




# Biometric Access Control System




# Biometric Time Attendance System — Support Multi Language



# Smart Attendance System Sending Notification To Mobile Phone



# Facial Recognition Video Intercom Access Control System





# Facial Recognition Elevator Control System



# QR Code Visitor Access Control System



# BioSecureCard

## Secure Your Biometrics Data




Complies with EU GDPR Standards



Encrypted CPU cards to prevent the replication of facial and fingerprint data.

# Membership Management System

## Suitable for GYM, Swimming pools, Libraries, and more.






# Message Reminder On Device



Public Message



Privacy Message




# Attendance Status Switching

## Auto Status Switch

In


Out



## Setting working time in machine

Event	Event message	Must
1	in	0
2	out	0
3	onduty	0
4	off duty	0
5		0

Event Schedule				
Automatically switch to Event during this time for assigned's Patch, no need to click				
		Start	End	Event
1	Event Schedule1	06:00	10:00	1
2	Event Schedule2	16:00	18:00	2
3	Event Schedule3			
4	Event Schedule4			
5	Event Schedule5			
6	Event Schedule6			
7	Event Schedule7			
8	Event Schedule8			



## Manual switch

Manually select the attendance status after facial recognition

# Multi-Tech Reading

EM, MIFARE, NFC, HID Prox, HID iCLASS, HID MIFARE, HID Prox/Indala, iso15693, DESFire, FELICA, NTAG210, NTAG213, NTAG215, NTAG216, MifareS50/S70, Utralight, FM1208, etc




# Intelligent Guard Tour System

To avoid some accidents caused by guards' dereliction of duty





# Four-Door Access Controller System (Integrating with Third-Party Devices)



Model	TM-S01	TM-S02	TM-S04
Product Name	Single Door Two Ways	2 Doors Two Ways	4 Doors Single Way
Exit	1	2	4
Fingerprint Capacity	5000		
Password Capacity	5000		
Card Capacity	5000 (30000 Optional)		
Record	110000		
Communication	TCP/IP、USB、RS485、Wegiang In/Out		
Distance	100 Meters		
Alarm	Fire		
Power	DC 12V , ≥100mA		
Dimension	215*105*35mm		

# Your Trusted OEM/ODM Partner

## Flexible Customization



Logo On Device



UI Customization



Logo On Boot Screen



Hardware Function Customization



Logo On Screensaver



Software Customization



Packaging Design



Appearance Customization

# AI

Discover The Power Of AI

## AI

Cutting edge technology



Rapid Development



Continuous Product Upgrades



Integrated Hardware, Software and Services



In-Dept Requirements Analysis



## R&D Capability

## Professional Services



End-to-end Solutions



Long-term Technical support



1 Year Product Warranty



International After-Sales Service



Partnership for Long Run



Quick Response



# Authentication Certificate



FC CE RoSH



National High-tech Enterprise



# AI Dynamic Face Recognition Time Attendance Access Control Terminal



**TM-AI01**

5 inch HD IPS  
Touch Screen

IP65 Waterproof  
Outdoor/Indoor  
both Aluminium  
alloy Case



**TM-AI02**

4.3 inch HD IPS  
Touch Screen

LED Frame  
Plastic Case  
Bell Button



**TM-AI03**

4.3 inch HD IPS  
Touch Screen

Support Face &  
ID/IC card  
optional



Face



Password



RFID Card



Infrared Fill-in



USB Disk



Wi-Fi



TCP/IP

## Specifications

Product name	AI Dynamic Face Recognition Time Attendance Access Control Terminal
Multiple Languages	English and other 16 types
Keypad	Touch keypad
Operation system	LINUX 3.10
CPU,NPU	1.2G Dual-Core ARM Cortex-A7, 600G ( 0.6T, 1.2T Optional )
RAM	256MB (512MB Optional ) DDR3
ROM	eMMC Flash 4GB (8GB Optional )
Binocular camera	2MP Colorful WDR+2MP Infrared live camera
Logs capacity	500000
Face Registration	Local operation: Enroll face with machine, import user photo with U disk Software operation: Import user photo to software, capture user photo with camera
Verification	Dynamic face recognition, password, ID/IC card optional
Face capacity	5000 (50000 optional)
Card Capacity	5000 (50000 optional), ID Card Standard, IC Card Optional
Password Capacity	5000 (50000 optional)
Face Recognition Accuracy	99.70%
Working temperature	-15°C~+45°C(storage temperature -40°C ~ +65°C)
Working humidity	20% ~ 90%(storage humidity 20% ~ 90±2%)
stand-by current	310mA
Working current	520mA
Working voltage	DC12V
Installation	Standard: Wall mount, desktop stand; Optional: bracket for turnstile, floor stand



# AI Dynamic Face Recognition Time Attendance Access Control Terminal



## TM-AI05

5 inch IPS  
Touch Screen

Both Desktop Bracket/  
Wall-mounted Bracket  
Screen Virtual  
Bell Button



## TM-AI06

4.3 inch IPS  
Touch Screen

Best Price  
Model



## TM-AI08

8 inch HD IPS  
Touch Screen

Mifare & EM  
card Both  
50000 Users



Face



Password



RFID Card



Infrared Fill-in



USB Disk



Wi-Fi



TCP/IP

## Specifications

Product name	AI Dynamic Face Recognition Time Attendance Access Control Terminal
Multiple Languages	English and other 16 types
Keypad	Touch keypad
Operation system	LINUX 3.10
CPU,NPU	1.2G Dual-Core ARM Cortex-A7, 600G ( 0.6T, 1.2T Optional )
RAM	256MB (512MB Optional ) DDR3
ROM	eMMC Flash 4GB (8GB Optional )
Binocular camera	2MP Colorful WDR+2MP Infrared live camera
Logs capacity	500000
Face Registration	Local operation: Enroll face with machine, import user photo with U disk Software operation: Import user photo to software, capture user photo with camera
Verification	Dynamic face recognition, password, ID/IC card optional
Face capacity	5000 (50000 optional)
Card Capacity	5000 (50000 optional), ID Card Standard, IC Card Optional
Password Capacity	5000 (50000 optional)
Face Recognition Accuracy	99.70%
Working temperature	-15°C~+45°C(storage temperature -40°C ~ +65°C)
Working humidity	20% ~ 90%(storage humidity 20% ~ 90±2%)
stand-by current	310mA
Working current	520mA
Working voltage	DC12V
Installation	Standard: Wall mount, desktop stand; Optional: bracket for turnstile, floor stand

# AI Dynamic Face Recognition Time Attendance Access Control Terminal

10.1  
inch



## TM-AI03F

5 inch IPS Touch Screen

Support Face & Fingerprint, Card

Fingerprint: 10000(50000 optional)




## TM-AI06F

4 inch IPS Touch Screen

Support Face & Fingerprint, CardTouch screen

Fingerprint: 10000



## TM-X1

10.1 inch IPS Touch Screen

Waterproof IP65  
Face recognition & Fingerprint ID/IC  
Fingerprint: 100000



## TM-AI07F

5 inch HD IPS Touch Screen

AI Face & Fingerprint Type  
Aluminium alloy Case

Fingerprint: 100000



## TM-AI18EF

8 inch HD IPS Touch Screen

AI Face & Fingerprint Type  
Aluminium alloy Case

Fingerprint: 100000



Face



Fingerprint



Password



RFID Card



Infrared Fill-in



USB Disk



Wi-Fi




## Specifications

Multiple Languages	English and other 16 types
Keypad	Touch keypad
Operation system	LINUX 3.10
CPU,NPU	1.2G Dual-Core ARM Cortex-A7, 600G ( 0.6T, 1.2T Optional )
RAM	256MB (512MB Optional ) DDR3
ROM	eMMC Flash 4GB (8GB Optional )
Binocular camera	2MP Colorful WDR+2MP Infrared live camera
Logs capacity	500000
Face Registration	Local operation: Enroll face with machine, import user photo with U disk Software operation: Import user photo to software, capture user photo with camera
Verification	Dynamic face recognition, password, ID/IC card optional
Face capacity	5000 (50000 optional)
Fingerprint capacity	10000
Card Capacity	5000 (50000 optional), ID Card Standard, IC Card Optional
Password Capacity	5000 (50000 optional)
Face Recognition Accuracy	99.70%
Working temperature	-15°C~+45°C(storage temperature -40°C ~ +65°C)
Working humidity	20% ~ 90%(storage humidity 20% ~ 90±2%)
stand-by current	310mA
Working current	520mA
Working voltage	DC12V
Installation	Standard: Wall mount, desktop stand; Optional: bracket for turnstile, floor stand

## Infrared Live Body Detection

Fast identify forehead, nose, chin, mouth, etc.





# ECO AI Dynamic Face Recognition Time Attendance Access Control Terminal



**TM-AI Face 11**

4.3 inch  
Touch Screen




**TM-AI26**

4.3 inch  
Touch Screen



**TM-AI20**

2.8 inch  
Touch Key



**TM-AI21**

4.0 inch  
Touch Screen

## Specifications

Keypad	Touch keypad
Operation system	LINUX 3.10
CPU	800M single-core ARM Cortex-A7
NPU	800G (0.8T) Hashrate
RAM, ROM	256M DDR3L, 4G EMMC
Camera	2MP color camera + 2MP infrared camera
Logs capacity	500000
Verification	Face recognition, password, ID Card(IC card optional)
Face capacity	5000
Card Capacity	5000
Password Capacity	5000
Face Recognition Accuracy	99.70%
Recognition Speed	≤0.2s
Recognition Distance	0.5~2.5 meters (0.5~1.5 meters with live face recognition on)
WDR	Wide dynamic range, support accurate face recognition under Strong light, dark light and backlight
USB	USB2.0x1 , Support U disk import/export data
Power supply	DC12V 1A
Built-in Battery (optional)	7.4V, 2000mA (AI Face 11)
Network Communication	TCP/IP, USB, Wifi
Free Attendance software	Local software and web based cloud software
Mask Detection	Support mask detection and face recognition with mask on
Access Control Interface	Lock output , Doorbell output/external ring , Weigand input/output
Environmental adaptability	Working temperature: 0~45°C Working humidity: 20% ~90%
Muti language	Support 20 national languages

# ECO AI Dynamic Face Recognition Time Attendance Access Control Terminal




**TM-AI Face 11F**

4.3 inch  
Touch Screen



**TM-AI26F**

4.3 inch  
Touch Screen



**TM-AI27F**

7.0 inch  
Touch Screen

## Specifications

Keypad	Touch keypad
Operation system	LINUX 3.10
CPU	800M single-core ARM Cortex-A7
NPU	800G (0.8T) Hashrate
RAM, ROM	256M DDR3L, 4G EMMC
Camera	2MP color camera + 2MP infrared camera
Logs capacity	500000
Verification	Face recognition, Fingerprint, password, ID Card(IC card optional)
Face capacity	5000
Card Capacity	5000
Password Capacity	5000
Fingerprint Capacity	5000
Face Recognition Accuracy	99.70%
Recognition Speed	≤0.2s
Recognition Distance	0.5~2.5 meters (0.5~1.5 meters with live face recognition on)
WDR	Wide dynamic range, support accurate face recognition under Strong light, dark light and backlight
USB	USB2.0x1 , Support U disk import/export data
Power supply	DC12V 1A
Built-in Battery (optional)	7.4V, 2000mA (AI Face 11F)
Network Communication	TCP/IP, USB, Wifi
Free Attendance software	Local software and web based cloud software
Mask Detection	Support mask detection and face recognition with mask on
Access Control Interface	Lock output , Doorbell output/external ring , Weigand input/output
Environmental adaptability	Working temperature: 0~45°C Working humidity: 20% ~90%
Muti language	Support 20 national languages



# Static Face / Fingerprint / Card Time Attendance

Different Case designs for your Option



Face



Fingerprint



Password



RFID Card

## Specifications

Product name	Face / Fingerprint / Card Time Attendance
Working	Network
Identification Style	Face, fingerprint, card, password
Identification Speed	<1 sec
FAR	<0.01
FAR	<0.0001
Face Capacity	1000/3000
Fingerprint Capacity	3000/5000
Card Capacity	3000/5000
Password Capacity	3000/5000
Record Capacity	100,000/300,000
Display	2.8 TFT/4.3 TFT
Language	English/Spanish/Turkish/Arabic/Thai/Persian and so on
Communication	TCP/IP/USB
Humidity	20%-60%
Temperature	0°C-40°C
Access control	Simple access control function for door open/close control
WG	1 Set WG In / Out
Output	Electric Lock
Voice	Boom, Dual LED
Power Supply	DC9V
Software	Free

# Fingerprint & Card Access Control

Different Case designs for your Option



**TFS28**

2.4" TFT Color LCD  
Fingerprint 3000  
Size 105\*105\*30mm



**TFS50**

Matellic case IP65 waterproof  
(Optional Ip67) ID&IC card  
Slim design: 140\*42\*18mm,  
for door with slim frame



**TFS28 Plus**

2.4" TFT Color LCD  
Fingerprint 3000  
Size 105\*105\*30mm



**TFS30**

2.4" TFT Color LCD  
Fingerprint 3000  
Size 190\*80\*33mm



**TFS70**

2.0" TFT Color LCD  
Fingerprint 3000  
Size 190\*80\*33mm



**TFS90**

2.8" TFT Color LCD  
Fingerprint 3000  
Size 190\*80\*42mm



## Specifications

Product name	Fingerprint & Card Access Control
Working	Online
Identification Style	Fingerprint, card, password
Identification Speed	<1 sec
FAR	<0.01
FAR	<0.0001
Fingerprint Capacity	3000
Card Capacity	3000
Password Capacity	3000
Record Capacity	200,000
Display	2.0 TFT/2.4 TFT
Language	English/Spanish/Turkish/Arabic/Thai/Persian and so on
Communication	TCP/IP/USB
Humidity	20%-60%
Temperature	0°C-40°C
Access control	Professional Simple access control function for door open/close control
Output	Electric Lock
Voice	Boom, Dual LED
Power Supply	DC12V
Software	Free



# Fingerprint & Card Time Attendance



**TM52**

Size 187\*131\*42mm



**TM20**

Size 198\*140\*40mm



**TM30**

Size 190\*180\*42mm



**TM60**

Size 189\*137\*50mm



**TM70**

Size 187\*131\*42mm



**TM50**

Size 185\*125\*38mm



**TM51**

Size 185\*125\*38mm



**TM58**

Size 180\*128\*40mm



**TM90**

Size 192\*136\*40mm



**TM1000**

Size 180\*130\*38mm

## Specifications


Product name	Fingerprint & Card Time Attendance
Working	Online
Identification Style	Fingerprint, card, password
Identification Speed	<1 sec
FAR	<0.01
FAR	<0.0001
Fingerprint Capacity	3000
Card Capacity	3000
Password Capacity	3000
Record Capacity	200,000
Display	2.4 / 2.8 TFT Color Screen
Language	English/Spanish/Turkish/Arabic/Thai/Persian and so on
Communication	TCP/IP/USB
Humidity	20%-60%
Temperature	0°C-40°C
Access control	Simple access control function for door open/close control
Output	Electric Lock
Voice	Boom, Dual LED
Power Supply	DC9V
Software	Free



Fingerprint




Password



RFID Card



TCP/IP



# Standalone Excel Report Time Attendance



**TM1800**  
Size 160\*130\*30mm



**TM2800**  
Size 160\*130\*30mm



**TM3800**  
Size 160\*130\*30mm



**TM4800**  
Size 160\*130\*30mm



**TM8000**  
Size 170\*130\*30mm

## Specifications


Product name	Fingerprint & Card Time Attendance
Working	Standalone
Identification Style	Fingerprint, card, password
Identification Speed	<0.8 sec
FAR	<0.01
FAR	<0.0001
Fingerprint Capacity	1000
Card Capacity	1000
Password Capacity	1000
Record Capacity	100,000
Display	2.4 / 2.8 TFT Color Screen
Languages	English/Spanish/Turkish/Arabic/Thai/French/Vietnamese and so on
Communication	FP+Card, PIN+Card,FP+PIN, FP+PIN+Card
Humidity	20%-60%
Temperature	0°C-40°C
Report	USB pen driver download reports in Excel or TXT file
Voice	Prompt voice of late arrival or early departure
Power Supply	DC5V



Fingerprint



Password



RFID Card



Automatic Report  
Generation



USB Flash Disk



# Standalone Fingerprint & Card Access Control



**TFS10**

Size:118\*118\*30mm



**TFS12A**

Size:86\*86\*30mm



**TFS16**

Size:140\*68\*34mm




**TAS10**

Size:118\*118\*30mm



## Specifications

Product name	Fingerprint & Card Time Attendance
Working	Standalone
Identification Style	Fingerprint, card, password
Identification Speed	<0.8 sec
FAR	<0.01
FAR	<0.0001
Fingerprint Capacity	1000
Card Capacity	1000
Password Capacity	1000
Record Capacity	100,000
Display	2.4 / 2.8 TFT Color Screen
Languages	English/Spanish/Turkish/Arabic/Thai/French/Vietnamese and so on
Communication	FP+Card, PIN+Card,FP+PIN, FP+PIN+Card
Humidity	20%-60%
Temperature	0°C-40°C
Access control	Simple access control function for door open/close control
Power Supply	DC12V





# QR Code Scanner For Access Control System

- ★ Read distance: 0~10cm(for QR code)
- ★ Code Type: QR code, 1D/2D barcode
- ★ working currency: <60MA
- ★ Card type: ID card, IC card, NFC card

- ★ Interface: Wiegand/RS232/RS485
- ★ Card read distance: 3~6cm
- ★ Decoding mode: Image decoding
- ★ Power supply: DC 12V



## Specifications

Product name	QR code access control card reader
Read distance	0~10cm(for QR code)
Code Type	QR code, 1D/2D barcode
working currency	< 60MA
Card type	ID card, IC card, NFC card
Interface	Wiegand/USB/RS232/RS485
Card read distance	3~6cm
Material	Tempered glass and Zinc alloy
Decoding mode	Image decoding
Power supply	DC 12V

# Tuya Fingerprint&RFID Access Control

Works with Smartphone by Tuya APP



**T12**

114\*75\*16mm

**TF2**

135\*47\*24mm

**TF3**

139\*70\*22mm

## Specifications

Card Type	EM Card(125khz), Mifare Card(13.56Mhz) optional
Keypad	Touch Keypad with Backlight
Material	Plastic
User Capacity	2000
Operating Voltage	12~24V
Standby Current	≤35mA
Waterproof	IP68
Operating Temperature	-35°C~55°C
Access Ways	Card, PIN, or combination
Door Bell	Support
Wiegand	WG 26/34, input&output
Admin Card	Support admin add card and admin delete card
Tuya APP Function	Remote unlock with APP, Add/edit/delete users in APP, Check unlock records, Generate recyclable temporary password and set validity period, Generate one-time use temporary password


# Proximity card time attendance

## Proximity card time attendance terminal

- ◆ Access Control, WG26
- ◆ Store your data on a USB flash drive
- ◆ Communication: USB , RS485, TCP/IP



**TFS800**



**TFS700**



**TFS500**




**TD300**

2.8" TFT Color LCD  
180\*128\*50mm



**TD800**

2.8" TFT Color LCD  
187\*131\*42mm



**TD900**

2.4" TFT Color LCD  
187\*131\*42mm

Download reports directly  
without software



## Specifications

Identification style	Card/PIN
Languages	Chinese , English, and more.
Card capacity	10000
Record capacity	100.000
LCD Size	2.4" TFT Color LCD / 2.8" TFT Color LCD
Communication	USB Cable/USB flash drive (optional TCP/IP)
Access control	Weigand 26 output and relay output
Voltage	DC5V / DC9V
Optional accessories	Optional battery



# Fingerprint Reader



**U5000**

95 (L) \* 52 (W) \* 36 (H) mm



**U6000**

74.8 (L) \* 50 (W) \* 30.8 (H) mm



Fingerprint



HF Cloud




USB 2.0



Win



Android



Lin



Dry Finger



Wet Finger



Lingt Texture Finger



Fake Fingerprint



High precision optical fingerprint sensor,  
rejects fake fingerprint




## Specifications

Hardware	
Physical size	-20 ° C to +70 ° C
Operating temperature	98%
Working humidity	5V
Operating voltage Working current	Up to 140mA
Software	Window,Android , Linx
OS	For Free, support ASP.NET, JAVA, Active X,
SDK	Web-based development etc
Fingerprint Sensor	
Image Size	256*288
Image Resolution	500DPI
Window Area	17mm * 19mm
Fidelity FRR	0.01%
False rate FAR	0.0001 %
Match Speed	<1s
Image Standard	WSQ , BMP and RAW, etc
Fingerprint Standard	ISO19794-2/-4, ANSI378
Durable	It can be used more than 1,000,000 times
Good anti-static	> 15KV, for dry weather
Communication	
Interface	USB/ Micro-USB (optional RS232/UART)

# Online Guard Tour System

**4G/GPRS/GPS real time guard tour patrol monitoring system with cloud software and mobile APP**



**TM-K2**

## Online Guard Tour System

4G/GPRS/GPS real time guard tour patrol monitoring system with cloud software and mobile APP



**TM-101Z**

## RFID Guard Patrol System With Management Software


**Application:**  
security guard, hospital, public security, hotel patrol, Petrochemical patrol, etc



**TM-101E**

## Economic Guard Tour System

2020 Popular Security Product Guard Tour Patrol System Standalone Software Download Data



## Touch Probe Security Guard Tour System



**TM-101X**

## Security Guard Tour Patrol Checkpoint



**TM-100T**

**TM-100**

# Long range Integrated UHF Reader/writer



UHF Ultrahigh frequency  
Long distance reading



Group tags reading, To read  
the tags at per time



IP65 Waterproof, Dust proof  
and lightning protection



**TM-SM06**

5-6M

Size: 227\*227\*60mm  
Weight: 2 Kg

**TM-SM109**

7-8M

Size: 260\*260\*60mm  
Weight: 3 Kg

**TM-SM15**

10-15M

Size: 450\*450\*50mm  
Weight: 4.5 Kg

**TM-SR20**

15-20M

Size: 215\*215\*50mm  
Weight: 0.8 Kg

**TM-SR40**

30-40M

Size: 445\*445\*35mm  
Weight: 2.55 Kg

## Specifications

Product name	Long range Integrated UHF Reader/writer
Working frequency	865 ~ 868MHz/902 ~ 928MHz
Reading distance	6-40 meters
Massive reading quantity	> 50 tags
Label protocol	Support ISO18000-6B, ISO18000-6C (EPC GEN2) protocol electronic label
Frequency hopping mode	broad spectrum frequency hopping (FHSS) or fixed frequency, which can be set by software
Working mode	automatic mode, trigger mode, interactive mode, etc.
RF power	0-30dBm (power software adjustable)
Antenna parameters	8-12dBi circularly polarized antenna (built-in)
Support interface	Standard RS232/RS485, Wiegand26/34 (Optional TCP/IP, WIFI, GPRS)
Working voltage	12V
Recognition prompt	beep or LED flash
Power consumption	<1W
Working temperature	-20°C ~ +70°C



# App Control Smart Biomtric Door Lock



Face Unlock



Fingerprint Unlock



Card Unlock



Password Unlock



Key Unlock



Door bell



Digital Door viewer



**TL20**

TT Lock/Tuya Wifi  
Fingerprint Apartment  
Metal Door Lock



**TL60**

Tuya Wifi  
3D Face & Fingerprint  
Glass Door lock



**B1**

TT Lock/Tuya Wifi  
Fingerprint Wooden/  
Metal Door Lock



**A9**

3D Face Recognition  
Full-Automatic  
Smart Lock



**B3**

TT Lock/Tuya Wifi  
Fingerprint  
Wooden Door Lock



**D1**


American Standard  
Code Button &  
Key Deadbolt  
door lock



**D2**


American Standard  
TT Lock/Tuya Wifi  
Fingerprint, Code  
Button & Key Deadbolt  
door lock

## ◆ 6068 Anti-theft Mortise




Standard 6068 (24×240mm) Security Hook 6068 (24×240mm) Cylinder 6068 (30×240mm)

## ◆ Swing Mortise (72 Series)



5072 (22×175mm) 5572 (22×235mm) 6072 (22×235mm)

## ◆ Single Latch & Deadbolt



# Card Access Control



## RFID Card Access Control



TDS10  
Size 155\*45\*20



TDS19  
Size 86\*86\*20



TDS03  
Size 86\*86\*18



TDS18  
Size 111\*61\*22



## Access control system accessories



TM-PS12V3A



TM-PS12V5A



TM-PS12V5AB  
(BATTERY)



TM-250  
Electric Bolt Lock



TM-280LED Magnetic  
lock ( two lines )



TM-20 Aluminum  
alloy door clip



TM280-U U  
support



TM280-ZL L type, Z type  
magnetic lock support



TM - 01A  
Stainless steel button



TM-02A  
touch button



TM-02A  
touch button



TM-05A  
Exit button



TM-06A Infrared  
Exit button



TM-07W Emergency  
door release



Remote button

# TiMY<sup>®</sup>



## Shenzhen Union Timmy Technology Co.,Ltd.

3rd Floor, Building A5, Silicon Valley Power Qinghu Park,  
Dahe Road, Qinghu Community, Longhua District, Shenzhen, China.

<http://www.sztimmy.net>

<http://www.timyteco.net>

Tel: +86 755 83875070

Email: [admin@sztimmy.com.cn](mailto:admin@sztimmy.com.cn)

Edition: SZ 2024, 01, EN